

# MVC PLUS DIMENSIONS

Ratings				Standard MVC3 Class E2 Soft Starter			Optional Soft Start Only				
Volts	Max. Amps	Nominal Max. HP	KW	Model	NEMA 12/3R *			Model	NEMA 12/3R *		
					H	W	D		H	W	D
2300	200	800	500	MVC3-23200-E-SWG	92	36	30	MVC3-23200-E	92	36	30
	400	1500	1000	MVC3-23400-E-SWG		36		MVC3-23400-E			
	600	2500	1900	MVC3-23600-E-SWG		72		MVC3-23600-E			
3300	200	1000	600	MVC3-33200-E-SWG	92	36	30	MVC3-33200-E	92	36	30
	400	1800	1200	MVC3-33400-E-SWG		36		MVC3-33400-E			
	600	3000	2200	MVC3-33600-E-SWG		72		MVC3-33600-E			
4160	200	1250	1000	MVC3-41200-E-SWG	92	36	30	MVC3-41200-E	92	36	30
	400	2500	2000	MVC3-41400-E-SWG		36		MVC3-41400-E			
	600	5000	3750	MVC3-41600-E-SWG		72		MVC3-41600-E			
6000/ 7200	200	2500	2000	MVC3-60200-E-SWG	92	72	30	MVC3-60200-E	92	36	30
	400	5000	3750	MVC3-60400-E-SWG				MVC3-60400-E			
	600	7500	5600	MVC3-60600-E-SWG				MVC3-60600-E		72	
11 - 15KV	300	7500	5700	MVC3-130300-E-SWG	Contact factory			Contact factory			
	600	15000	11000	MVC3-130600-E-SWG	Contact factory			Contact factory			

\*Dimensions are in inches.

